

## CASED-HOLE LOGGING

# INLINE SPINNER



MAKING INTERVENTION  
**SMARTER**

The Inline Spinner (ILS) is a compact flowmeter with the spinner blade protected by a shroud.

## FEATURES

- Leak detection
- Often used in conjunction with a fullbore flowmeter
- Often run as a backup spinner in the toolstring
- Spinner blade is protected by a shroud and less
- Susceptible to damage
- Precision roller bearings
- Low threshold
- Combinable with other GE Ultrawire™ tools
- Memory or surface read-out operation

SERVICE NAME	ILS021	ILS022
<b>Length</b>	439 mm / 17.3 in	439 mm / 17.3 in
<b>Weight</b>	3 kg / 6.5 lbs	3.1 kg / 6.8 lbs
<b>OD</b>	43 mm / 1.688 in	54 mm / 2.125 in
<b>Maximum fluid velocity</b>	15 m/s / 3000 ft/min	15 m/s / 3000 ft/min
<b>Spinner threshold</b>	0.06 m/s / 12 ft/min	0.06 m/s / 12 ft/min
<b>Maximum pressure</b>	1030 bar / 15 000 psi	1030 bar / 15 000 psi
<b>Maximum temperature</b>	177 °C / 350 °F	177 °C / 350 °F